

Front



Inside

A-63A-SX01-Gateway

AUX GROUP

Established in 1986, AUX Group is an enterprise which covers 5 industries. It ranked China's top 500 enterprises for consecutive years, 40000+ employees keep AUX fast development for recent years.

39 Years History	\$12.6 Billion Revenue in 2024	5 Business Industries
\$ 9.6 Billion Assets	500 China's Top	40000+ Employees

AUXSOL

WIN A GREEN FUTURE TOGETHER

Ningbo AUX Solar Import & Export Co., Ltd.


No. 518, Xinmei Road, Yinzhou District, Ningbo City, zhejiang Province, China



✉ info@auxsol.com
 🌐 www.auxsol.com
 ☎ +86 0574-8765 2201

Technical Specification		A-63A-SX01-Gateway
General Data		
Dimensions (H * W * D)	725*605*90	
Weight kG	32.5	
Performance		
AC Voltage (nominal)	220/230/240 V L/N+PE	
Max. current (from Grid)	63 A	
Max. current (from Inverter)	60 A	
Max. current (to backed-up load)	63 A	
Max. current (to non-backed-up load) 1	63 A	
Low-voltage ride-through	Supported	
Switchover time	≤ 20 ms (in Seamless Mode)	
Bypass operation mode Manual	manual	
Interface		
Power output	9.5-13.2V @ 100mA, ≤ 3m	
WAN	10/100 Mbps, ≤ 100 m	
WLAN	AP Mode, 802.11b/g/n (2.412 GHz-2.484 GHz)	
RS485	9600/19200/115200 bps, × 10, ≤ 50m	
Digital input	×4, ≤ 20 m	
Digital output	×4, ≤ 20 m	
Measurement Range		
Current range	≤ 63 A	
Voltage range	165-288V(Phase voltage),286-498V(Line voltage)	
Device Management		
inverter	ASG-5/6/8/10/12/15/20TL-ZH	
EV chargers	SXACG11 A322Q11;SXACG11 A163Q11;SXACC12 A323Q13	
Heat pump ²	AUX R290	
RS485 device	up to 10	
Environment		
Noise emission	≤ 29 dBA	
Cooling method	natural cooling	
Relative humidity range	5%-95% RH (non condensing)	
Max. operating altitude	4000m (derated over 2000m)	
IP rating	IP54	
Operating temperature range	-25°C-50°C	

Note: The specification and key features described in this datasheet may deviate slightly and are not guaranteed. AUXSOL reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the latest version of the datasheet, any commercial contracts that may be signed will be based on the most recent version at the moment of signing the contract.



ABI-Gateway

AUX GROUP

Established in 1986, AUX Group is an enterprise which covers 5 industries. It ranked China's top 500 enterprises for consecutive years, 40000+ employees keep AUX fast development for recent years.

39 Years History	\$12.6 Billion Revenue in 2024	5 Business Industries
\$ 9.6 Billion Assets	500 China's Top	40000+ Employees

AUXSOL

WIN A GREEN FUTURE TOGETHER

Ningbo AUX Solar Import & Export Co., Ltd.

No. 518, Xinmei Road, Yinzhou District, Ningbo City, zhejiang Province, China



✉ info@auxsol.com
 🌐 www.auxsol.com
 ☎ +86 0574-8765 2201

Product Model		ABI-Gateway
Hardware parameters		
System		LINUX operating system (Debian 6.1.33)
CPU		4-core, 1.4GHz
Random access memory (RAM)		2G DDR4
Storage		8GB eMMC
Ethernet		2-way 10M/100M adaptive (RJ45)
Serial port (computing)		10-way, RS485
IO port		4-way DI, 4-way relay-isolated DO
SD card		Support up to 128G
RTC		Built-in real-time clock
USB Burning		1 channel USB2.0
LED		POWER, WIFI, NET
WIFI		1×IEEE 802.11a/b/g/n/ac standard protocols
Bluetooth		5.0 Standard Protocols
Port Specifications		
WLAN		AP+STA, 802.11b/g/n (2.412-2.484GHz)
RS485		9600-115200bps, ≤ 1000m
USB		USB2.0/480Mbps
LAN/WAN		10/100Mbps, ≤ 100m
DI port		Passive dry contact ≤ 20m
DO port		30V/2A (ON) ≤ 20m
Electrical Specifications		
Rated Input		12VDC/1A
Input Voltage Range		9~ 18VDC
Power protection		Surge protection
Device management		
Smart meter		≥1/serial port
Inverter		≥16/serial port
EV Charger		≥1/serial port
Heat pump		≥1/serial port
Environment		
Operating temperature		-25~ +60 °C
Environment temperature		-40~ +85 °C
Environment humidity		5%~ 95% RH (no condensation)
Maximum working altitude		4000m
IP rating		IP20
Structural		
Dimensions (W D×× H)		175mm*128mm*58mm
weights		857g
material		Stainless steel201